



ITT

B3GV

Wastewater

Goulds Pumps

3GV up to 20 HP

Submersible Vortex Sewage Pump

Dual Seal with Seal Sensor Probe



Shown with optional stand




Goulds Pumps is a brand of ITT Corporation.

www.goulds.com

Engineered for life

FEATURES

- **Impeller:** Ductile iron, vortex style, dynamically balanced with pump out vanes for mechanical seal protection.
- **Casing:** Heavy duty cast iron, volute type for maximum efficiency. 3" flange conforms to 125 # ANSI standard. Connects to A10-30 guide rail system.
- **Dual Mechanical Seals:** Silicon carbide vs. silicon carbide outer seal and ceramic vs. carbon inner seal, stainless steel metal parts, BUNA-N elastomers. Upper and lower shaft seals are positioned independently and are separated by an oil-filled chamber.
- **Seal Sensor Probe:** Located in oil-filled chamber. If pumpage should begin to leak past lower seal it indicates to pump control panel a fault has occurred. **Requires Seal Fail Circuit in the control panel.**
- **Standard High Temperature Sensor:** Requires optional high temperature in panel.
- **Shaft:** Corrosion resistant, 400 series stainless steel. Key and impeller bolt on all models to guard against component damage on accidental reverse rotation.
- **Fasteners:** 300 series stainless steel.
- Capable of running dry without damage to components.
- Designed for continuous operation, when fully submerged.



ITT

GOULDS PUMPS Wastewater

APPLICATIONS

Used in a variety of residential, commercial and industrial applications such as:

- Sewage systems
- Flood and pollution control
- Dewatering/Effluent
- Farms
- Hospitals
- Trailer courts
- Motels

SPECIFICATIONS

Pump:

- Maximum solid size: 2" / 2.5"
- Discharge size: 3", 125 # ANSI flange
- Maximum capacity: 400 GPM
- Maximum total head: 160 feet
- 300 Series stainless steel fasteners
- 50' Power cord
- Standard silicon carbide/silicon carbide outer seal

Motor:

- Maximum ambient temperature: 104° F (40° C) continuous duty, 140° F (60° C) intermittent duty
- Rated for continuous duty when fully submerged
- Insulation: Class F
- 60 Hertz
- Single row ball bearings
- 400 Series stainless steel keyed shaft
- Requires external motor components for single phase (not included)
- Requires overload protection in panel (not included)
- Includes high temperature sensor

AIR-FILLED MOTOR

- Efficient heat dissipation
- Run dry capability
- **Class F insulation**
- **Designed for Continuous Operation:** Pump ratings are within the motor manufacturer's recommended working limits and can be operated continuously without damage when fully submerged.
- **Bearings:** Upper and lower heavy duty ball bearing construction for precision positioning of parts and to carry thrust loads.
- High temperature sensor
- **Cable:** Severe duty rated, oil and water resistant. 50 foot standard.
- **O-ring:** Assures positive sealing against contaminants and oil leakage.



ITT

GOULDS PUMPS Wastewater

MODEL AND MOTOR INFORMATION

Part No.	Discharge	HP	Phase	Volts	RPM	Impeller Diameter	Power Cable	Resistance		Weight (lbs.)	Solids	AMP Draw	
								Start	Line-Line				
3GVA72B3AF	3"	2.3	3	230	1750	4.72	14/7	—	2.2	95	2	7.4	
3GVA72B4AF				460				—	8.6			3.5	
3GVA72C3AF		3.4		230		—		2.2	10.4				
3GVA72C4AF				460		—		8.6	5				
3GVB72A0AF	3"	1	1*	115	1750	5.43	14/7	4.0	1.8	83	2.5	10.5	
3GVB72A1AF				230				12.6	5.3			5.5	
3GVB72A3AF			3	460		—		6.0	3.7				
3GVB72A4AF				230		—		24.0	1.8				
3GVB72C3AF		3.4	3	230	3500	6.69	14/7	—	2.2	124	2.5	10.4	
3GVB72C4AF				460				—	8.6			5	
3GVB72E3AF		5.4	3	230	1750	7.68	14/7	—	3.2	124	2.5	16	
3GVB72E4AF				460				—	4.3			7.7	
3GVB71B1AF		3"	2.8	1*	230	3500	3.74	14/4	2.4	0.7	83	2.5	12
3GVB71B3AF			2.3	3	230			4.65	14/7	—	2.3		91
3GVB71B4AF					460		—			9.2	3.3		
3GVB71D3AF			4	3	230		4.92	14/7	—	1.2	95		11.7
3GVB71D4AF					460	—			4.4	5.6			
3GVB71F3AF			6.2	3	230	1750	5.516	12/7	—	1.8	264	2.5	17.3
3GVB71F4AF	460				14/7			—	2.3	8.3			
3GVB71L4AF	19.7		460	6.698	10/4-14/4	—	—	264	24.1				
3GVB71J4AF	14			6.107	12/4-14/4	—	—	229	17.3				
3GVB71G4AF	7.8		1750	5.516	8.865	14/7	—	—	196	9.9			
3GVB72H4AF	11.5			8.865			—	—	203	15.3			
3GVB72G4AF	7.8		8.274	—	—	196	10.9						

* Requires panel mounted motor capacitors and overload protection. (Not supplied with pump.)

NOMENCLATURE DESCRIPTION

1st, 2nd, 3rd and 4th Character –

Discharge Size and Type

3GVA = 3" discharge, 2" solids handling, dual seal with seal fail probe in pump.

3GVB = 3" discharge, 2.5" solids handling, dual seal with seal fail probe in pump.

5th Character – Mechanical Seals

7 = Silicon carbide/silicon carbide/BUNA – lower seal and carbon/ceramic/BUNA – upper seal (standard)

6th Character – Cycle/RPM

1 = 60 Hz/3500 RPM

2 = 60 Hz/1750 RPM

7th Character – Horsepower

A = 1.0 HP E = 5.4 HP H = 11.5 HP

B = 2.3/2.8 HP F = 6.2 HP J = 14.0 HP

C = 3.4 HP G = 7.8 HP L = 19.7 HP

8th Character – Phase/Voltage

0 = single phase, 115 V 3 = three phase, 230 V


1 = single phase, 230 V 4 = three phase, 460 V

9th Character – Impeller Diameter

A = maximum impeller

10th Character – Cord Length (Power and Sensor)

F = 50'



ITT

Wastewater

APPLICATION DATA

Maximum Solid Size	2" / 2½"
Maximum Working Pressure	150 PSI
Maximum Submergence	66 feet
Minimum Submergence	Fully submerged for continuous operation
Maximum Environmental Temperature	40° C (104° F) continuous operation

CONSTRUCTION DETAILS

Power and Sensor Cable	12/7, type: three phase		
	14/7, type: single and three phase		
Motor Cover	Gray Cast Iron – ASTM A48 Class 35		
Seal/Bearing Housing	Gray Cast Iron – ASTM A48 Class 35		
Casing	Gray Cast Iron – ASTM A48 Class 35		
Impeller	Ductile Iron – ASTM A395 Gr. 60-46-18		
Motor Shaft	AISI 400 Series Stainless Steel		
Motor Design	Air filled Class F		
Single Phase Capacitors	HP	Volt	Rating of Capacitors
	1	115	50 mfd/450
	1	230	25 mfd/450
	2.8	230	50 mfd/450
Motor Overload Protection	Single/Three Phase: require ambient compensated Class 10, quick trip overloads in the control panel.		
Motor Seal Fail / High Temp. (Moisture) Detection	Seal fail sensor and high temp. in an oil-filled seal chamber. Connect to optional relays in control panel.		
External Hardware	300 Series Stainless Steel		
Impeller Type	Vortex with pump out vanes on back shroud		
Oil Capacity – Seal Chamber	20.3 ounces		

STANDARD PARTS

Ball Bearing	Upper	Single row ball – 6304 2RS C3
	Lower	Single row ball – 6305 2RS C3
Mechanical Seals – Standard	Upper	Carbon/Ceramic
	Lower	Silicon Carbon
O-Ring – Stuffing	BUNA-N	
O-Ring – Motor Cover	BUNA-N	

MATERIALS OF CONSTRUCTION

Item No.	Part Name	Material Standard				
		1	Impeller	Ductile Iron GR 60		
2	Castings	Cast Iron CI - 35				
3	Shaft-keyed	400 Series SS				
4	Fasteners	300 Series SS				
5	Ball bearings	Steel				
6	Cord	SOW, 50 feet				
7	O-ring	BUNA-N				
8	Outer Mech. Seal	Service	Rotary	Stationary	Elasto-mers	Metal Parts
		STD	Mild abrasives	Silicon Carbide	BUNA-N	300 Series SS
	Lower Mech. Seal	Service	Rotary	Stationary	Elasto-mers	Metal Parts
		STD	Mild abrasives	Carbon / Ceramic	BUNA-N	300 Series SS



Goolds Pumps and the ITT Engineered Blocks Symbol are registered trademarks and tradenames of ITT Corporation.

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

B3GV March, 2009

Copyright (c) 2009 ITT Corporation

Engineered for life