



AquaBoost™ Advanced Packaged System Quick Ship Program



When your customer needs a quick boost, we're ready to help.

The AquaBoost Advanced Packaged System is a compact, easy-to-install and maintain package specifically designed for applications where sufficient water main pressure is not available or elevation is a problem. It provides intelligent pumping with maximum value, proven reliability, superior energy efficiency and better system protection. What's more, when you order an AquaBoost Advanced Packaged System before 1 p.m. CST, it will be shipped within three business days (72 hours).

Place your order today! Call 1-844-995-7867 and press 1. Or email AWS_BoosterOrders@xylem.com.

Specifications

- Fabricated with 316L stainless steel NPE centrifugal pumps
- 316 stainless steel manifolds feature grooved connections
- Available configurations:
 - Simplex - 20 to 110 GPM (boost up to 55 psig)
 - Duplex - up to 220 GPM (boost up to 55 psig)
- Standard TEFC Premium Efficiency Motors
- 208-230V, 380V, 460V, and 575V models available
- Built in system protections (pump run out, dry run, overvoltage, undervoltage, blocked suction, cavitation, NPSHa, phase loss, short circuit, transducer failure and motor current overload)
- Programmable lead/lag alternation (duplex) and system pressure
- Liquid and ambient temperatures up to 104° F
- Fault detection and alarm notification
- Motor run relay
- Branch isolation valves (duplex systems)
- UL listed as packaged pumping systems
- Certified ANSI/NSF-61

AquaBoost™ ADVANCED PACKAGED SYSTEM QUICK SHIP PROGRAM

AquaBoost Advanced Naming System:

AquaBoost Advanced Naming System				
Model Numbers	# of pumps	Hydraulic	HP	Voltage/Phase
AQA	1 = simplex	A = 1ST	15 = 1½	A = 208/230/1
	2 = duplex	B = 2ST	20 = 2	B = 208/230/3
			30 = 3	C = 380/3
			40 = 4	D = 460/3
			50 = 5	E = 575/3

AquaBoost Advanced Models Available for Quick Ship:



Quick Ship Package Information						
Part Number	Description	Length (In)	Width (In)	Height (In)	Weight (lbs)	
AQA1B20B	AQA SIMPLEX 2ST 2HP 208/230/3	22.75	23.25	29	156.9	
AQA1B50A	AQA SIMPLEX 2ST 5HP 208/230/1	24.875	27.5	29	302.1	
AQA1B50D	AQA SIMPLEX 2ST 5HP 460/3	22.75	27.25	29	172.3	
AQA2B20B	AQA DUPLEX 2ST 2HP 208/230/3	35.25	38	36	321.7	
AQA2B20D	AQA DUPLEX 2ST 2HP 460/3	35.25	38	36	321.7	
AQA2B30B	AQA DUPLEX 2ST 3HP 208/230/3	35.25	38	36	345.9	
AQA2B30D	AQA DUPLEX 2ST 3HP 460/3	35.25	38	36	345.9	
AQA2B50B	AQA DUPLEX 2ST 5HP 208/230/3	35.25	42	36	367.5	
AQA2B50D	AQA DUPLEX 2ST 5HP 460/3	35.25	42	36	352.5	
AQA2B50E	AQA DUPLEX 2ST 5HP 575/3	35.25	41	36	356.5	

Please note: system isolation valves for duplex systems must be supplied by the installer.

To view the full AquaBoost product line please visit www.xylem.com/goulds

Place your order today! Call 1-844-995-7867 and press 1. Or email AWS_BoosterOrders@xylem.com

Xylem Product Cybersecurity

Xylem values your system security and the availability of your critical services. For more information on Xylem cybersecurity practices or to contact the cybersecurity team please visit xylem.com/security.



Xylem Inc.
 Phone: (844) XYL-PUMP [844-995-7867]
 Fax: (888) 322-5877
www.xylem.com/goulds

Goulds is a registered trademark of Goulds Pumps, Inc. and is used under license.
 AquaBoost is a trademark of Xylem Inc. or one of its subsidiaries.
 © 2020 Xylem Inc. AQBSTADVSALES R1 July 2020

