VIKING LID-EASE®

SIMPLEX BASKET STRAINERS
CAST IRON OR STAINLESS STEEL CONSTRUCTION



SIZES 3/4", 1", 11/2", 2", 3", 4", 6", 8"





MATERIALS
Cast Iron, Stainless Steel




PROTECTION FOR PUMPS &

DOWNSTREAM

SYSTEMS

When the basket requires cleaning, simply vent system pressure, remove the lid and withdraw the basket from the top. Foreign matter contained in the basket will not drop back into the system.



FEATURES & BENEFITS

- · Quarter-turn, easy opening breech-lock lid simplifies routine cleaning
- Inclined basket design provides low pressure drop for high system efficiency
- Top basket removal eliminates the need to drain the strainer and minimizes product loss
- · Optional magnetic inserts are available for trapping ferrous particles
- · Optional differential pressure indicators optimize cleaning intervals

OPTIONS

- · Basket mesh from 10 to 100
- Magnetic inserts
- · Differential pressure indicators





PERFORMANCE

MODELS		SPECIFICATIONS									
		Nominal Capacity Suction Rating		Rated System Pressure		Approximate Shipping Weight		Standard Port			
CASTIRON	Size	GPM	m³/h	PSI	BAR	Lbs	Kg	Type*	Inches		
	F-1007	20	5	200	14	7	3	Т	3/4		
	F-1010	30	7	200	14	7	3	T	1		
	F-1015	50	11	200	14	9	4	T	1-1/2		
	F-1020	100	23	200	14	16	7	F, T	2		
	F-1030	200	45	125	8.5	40	18	F, T	3		
	F-1040	400	91	125	8.5	73	33	F	4		
	F-1060	800	182	125	8.5	120	54	F	6		
	F-1080	1,500	340	125	8.5	300	136	F	8		
STAINLESS STEEL	F-1007	20	5	200	14	7	3	Т	3/4		
	F-1010	30	7	200	14	7	3	Т	11		
	F-1015	50	11	200	14	10	4.5	T	1-1/2		
	F-1020	100	23	200	14	20	9	F, T	2		
	F-1030	200	45	125	8.5	44	20	F	3		
	F-1040	400	91	125	8.5	77	35	F	4		
	F-1060	800	182	125	8.5	128	58	F	6		

^{*} Port Type Options: F = Flanged, T = Tapped (NPT)

MESH SPECIFICATIONS

MESH	NO MESH (Perforated Basket Only)	10	20	40	60	80	100
OPENING (INCHES)	.156 (Sizes ³ / ₄ " - 1½") .188 (Sizes 2" - 8")	.075	.034	.015	.009	.007	.0055
OPENING (MICRONS)	3962 (Sizes ³ / ₄ " - 1½") 4775 (Sizes 2" - 8")	1,910	860	380	230	190	140

VIKING QUALITY CONSTRUCTION

- · High-quality, easy-to-clean simplex strainers
- · Designed for chemical, petrochemical and most general fluid-flow applications
- Tapped or flanged porting are available for 3/4, 1, 11/2, 2, 3, 4, 6 and 8 inch piping
- · SS basket and screen are available in no mesh, 10, 20, 40, 60, 80 or 100 mesh
- Nominal capacities range from 20 to 1.500 GPM
- · Pressures up to 200 PSI
- · Strainer bodies & lids are available in cast iron or stainless steel



Baskets shown with optional magnetic inserts to trap fine ferrous particles

LOW PRESSURE DROP

Viking Lid-Ease Strainers are designed for minimal pressure drop through the unit. Pressure drop is minimized by the inclined position of the strainer basket adjacent to the porting. This provides smooth flow patterns not found in conventional basket type strainers.

EASY TO CLEAN

complete draining, if required.

No special tools are needed for lid removal. A simple lid rotation disengages the breech-lock lid to permit easy removal of the basket. The basket is removed from the top of the strainer to eliminate foreign matter from dropping back into the line when the strainer is cleaned. The strainers are equipped with a drain plug for

The light-weight and small overall dimensions make it possible to install Viking Lid-Ease Line Strainers in systems that cannot accommodate larger strainers of equal porting size.

Contact Your Stocking Distributor Today

VIKING PUMP, INC.

A Unit of IDEX Corporation 406 State Street Cedar Falls, Iowa 50613 U.S.A. vikingpump.com

United States

Cedar Falls, Iowa Phone: (319) 266-1741

Canada vikingpumpcanada.com

VIKING PUMP

Windsor, Ontario Phone: (519) 256-5438

Europe & Africa vikingpump.com

Asia-Pacific

China - Shanghai Phone: +86-21-5241-5599 India - Mumbai Phone: +91-22-6643-5563 Singapore Phone: +65-6684-7305

Middle East **Dubai, UAE** e: +971 4 2600300 Latin America

Australia & New Zealand

